## ELASTOSIL® LR 3003/50 A/B

Silicone

## Wacker Chemie AG

## **Technical Data**

## Product Description

Silicone Rubber, LSR

Molded Seals, Plastics and Rubber Processing Molded Parts, Technical, Plastics and Rubber Processing Molded Parts, Food Contact, Plastics and Rubber Processing Molded Parts, Automotive, Plastics and Rubber Processing Vibration Dampers, Automotive & Transportation

General			
Material Status	Commercial: Active		
UL Yellow Card <sup>1</sup>	• E75704-249839		
Search for UL Yellow Card	<ul> <li>Wacker Chemie AG</li> </ul>		
Availability	<ul><li> Africa &amp; Middle East</li><li> Asia Pacific</li></ul>	<ul><li>Europe</li><li>Latin America</li></ul>	North America
Features	<ul> <li>Food Contact Acceptable</li> </ul>	General Purpose	
Uses	<ul><li>Automotive Applications</li><li>Automotive Under the Hood</li></ul>	<ul><li>Gaskets</li><li>Membranes</li></ul>	<ul><li>Seals</li><li>Valves/Valve Parts</li></ul>
Processing Method	<ul> <li>Injection Molding</li> </ul>	Liquid Injection Molding (LIM)	

Uncured Properties	Nominal Value (English)	Nominal Value (SI)	Test Method
Color	Clear/Transparent	Clear/Transparent	
Density	1.13 g/cm <sup>3</sup>	1.13 g/cm <sup>3</sup>	ISO 1183
Viscosity	370 Pa·s	370 Pa·s	DIN 53019
Cured Properties	Nominal Value (English)	Nominal Value (SI)	Test Method
Shore Hardness (Shore A)	50	50	DIN 53505
Tensile Strength	1440 psi	9.90 MPa	DIN 53504
Tensile Elongation at Break	480 %	480 %	DIN 53504
Compression Set	13 %	13 %	DIN ISO 815-E
Tear Strength	166 lbf/in	29.0 kN/m	ASTM D624B
Rebound Resilience	62 %	62 %	DIN 53512
Electric Strength	580 V/mil	23 kV/mm	DIN IEC 243
Volume Resistivity	5.0E+15 ohms cm	5.0E+15 ohms cm	DIN IEC 93
Dissipation Factor (50 Hz)	2.0E-3	2.0E-3	DIN VDE 0303

**Notes** 

<sup>1</sup> A UL Yellow Card contains UL-verified flammability and electrical characteristics. UL Prospector continually works to link Yellow Cards to individual plastic materials in Prospector, however this list may not include all of the appropriate links. It is important that you verify the association between these Yellow Cards and the plastic material found in Prospector. For a complete listing of Yellow Cards, visit the UL Yellow Card Search.

<sup>2</sup> Typical properties: these are not to be construed as specifications.



1 of '

The information presented here was acquired by UL from the producer of the product or material or original information provider. However, UL assumes no responsibility or liability for the accuracy of the information contained on this website and strongly encourages that upon final product or material selection information is validated with the manufacturer. This website provides links to other websites owned by third parties. The content of such third party sites is not within our control, and we cannot and will not take responsibility for the information or content. R®

www.ulprospector.com

PROSPECTO